



SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifier: Ceramic Glazed Tile **Hand Written and Cursive Series**

Product use: Hand Crafted Ceramic Tile recommended for walls in interiors, for a residential use, This product uses a variety of aggregate components mixed together in a designed configuration. After milling the ingredients, forming and glazing these tiles are fired at 1130°C to become a finished product.

Manufacturer: Astor TileWorks SA De CV

Camino real a Monclova # 4700

Parque industrial

Ramos Arizpe, Coah. Mexico

Phone number :011-528-444-488-3772

Emergency phone number: 011-528-444-488-3771

www.astortileworks.com

Recommended use: Hand Made Ceramic Tile Recommended for residential use

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW – Non-hazardous PRODUCT as a intact tile.

NFPA Rating: Health - 0, Flammability - 0, Reactivity - 0

NFPA Definitions: (0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme).

Potential Health Effects: None for intact tile. Inhalation and potential exposure to eyes, hands, or other body parts if contact is made with broken, and/or during procedures involving the cutting of tiles, and/or for operations involving the removal of installed tiles.

Inhalation: This product may represent an inhalation hazard during cutting or removal with creation of respirable dust.

Ingestion: This product does not represent an ingestion hazard.

Skin Contact: Dust maybe irritating to skin

Eye Contact: Dust may cause irritation

Chronic Exposure: No chronic effects for intact tiles. Long-term, continual exposure to Respirable crystalline silica at or above allowable occupational exposure limits may lead to the development of silicosis.

Aggravation of Pre-existing Conditions: Pre-existing skin and respiratory problems.

Carcinogenicity: Silica is listed by the NTP, IARC, or regulated by OSHA as a carcinogen. We recommend wet cutting or the score and snap method during the installation process. Do not dry cut using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

3. COMPOSITION / INFORMATION ON INGREDIENTS:

Chemical Name	Percent	CAS Number	ACGIH TLV	OSHA PEL
Clay		45 – 65% N.E.	N.E.	N.E.
Feldspar	30 – 45%	68476-25-5	0.025 mg/m ³	10 mg/m ³
Recovered Tile Material	0 – 5%	N.E.	0.025 mg/m ³	10 mg/m ³
Pigment	0 – 5%	N.E.	N.E.	N.E.

Tile products are mixtures of naturally occurring minerals that have been mixed with water and cured. Tiles are manufactured in various shapes, sizes, and colors. These tiles do not contain asbestos. Under normal conditions these products do not release hazardous materials after installation and are not considered hazardous waste should disposal be necessary.

The tiles are odorless, stable, nonflammable, and pose no immediate hazard to health. However, respiratory, hand and eye protection may be needed to prevent excess exposure to airborne particulates if dust is produced by cutting tiles or if dust is produced by any other operation, including removal.

Crystalline Silica as quartz CAS# 14808-60-7

Airborne Exposure Limits: Silica Dust

	OSHA PEL	ACGIH TLV
Respirable Fraction	10 mg/m ³	0.025 mg/m ³

HAZARDS DISCLOSURE: This product contains known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200. As defined under Sara 311 and 312, this product contains known hazardous materials.

This product does not contain asbestos or polychlorinated biphenyls.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air if exposed to large amounts of dust.

Ingestion: Not expected as a result of this product.

Skin Contact: Wash thoroughly after working with tiles.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (PMCC): Not Flammable

Auto-ignition temperature: Not established

Flammable limits in air % by volume:

LEL: Not established

UEL: Not established

Explosion: N/A

Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire.

Special Fire Fighting Procedures: In the event of a fire, wear full protective clothing and NIOSH- approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Pick-up for re-use or recycle.

7. HANDLING AND STORAGE

Storage Temperature (min/max): 50°F (10°C.) to 100°F (38°C)

Shelf Life: N/A

HANDLING (PERSONNEL): Handle in accordance with good hygiene and safety procedures. We recommend wet cutting or the score and snap method during the installation process. Do not dry cut using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

8. STORAGE PRECAUTIONS: None Established.

9. EXPOSURE CONTROLS / PERSONAL PROTECTION

Airborne Exposure Limits:

Airborne Exposure Limits: Silica Dust

Wet cutting methods and exposure control methods set forth in Table 1 of 29 CFR § 1926.1153 are recommended.

	OSHA PEL	ACGIH TLV
Respirable Fraction	10 mg/m ³	0.025 mg/m ³

Ventilation System: Always work in a well ventilated area.

Personal Respirators (NIOSH Approved): None required if dust is below permissible exposure levels.

Skin Protection: Observe good industrial hygiene practices.

Eye Protection: Always wear safety glasses when working with this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Solid **COLOR:** Varies

ODOR: Odorless **SPECIFIC GRAVITY:** N/A

SOLUBILITY IN WATER: PH: N/A

MELTING/FREEZING POINT: N/A **BOILING POINT:** N/A

EVAPORATION RATE (BuAc=1): N/A **VISCOSITY:** N/A

AUTOIGNITION TEMPERATURE: N/A **VAPOR DENSITY (Air=1):** N/A

% VOLATILES BY VOLUME @ 21°C (70°F): N/A **VAPOR PRESSURE (mm Hg):** N/A

VOLATILE ORGANIC COMPOUNDS (VOC #/gal): N/A

10. STABILITY AND REACTIVITY

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products: None

Hazardous Polymerization: Will not occur.

Incompatibilities: None known.

Conditions to Avoid: None known.

11. TOXICOLOGICAL INFORMATION

Toxicity Data:

Product Name	Oral, LD50, Rat	Dermal	Inhalation	
Tile (Contains Silica)	>22,500 mg/kg		N/A	N/A

Cancer Lists

Ingredient	---NTP Carcinogen---	IARC Category
Silica	Known Anticipated YES YES	A4

12. ECOLOGICAL INFORMATION

Environmental Fate: No Data Available

Environmental Toxicity: No Data Available

13. DISPOSAL CONSIDERATIONS

Dispose of container and unused contents in accordance with federal, state and local requirements.

14. TRANSPORTATION INFORMATION

Domestic (Land, D.O.T.) International (Water, I.M.O. & Air, I.C.A.O.)

SHIPPING NAME:	Non-Regulated Material				
PRODUCT LABEL:	Glazed/Technical Tile	UN NUMBER:	N/A		
ADR:	N/A	MO CLASS:	N/A		
D.O.T. HAZARD CLASS:	N/A	PACKING GROUP:	N/A		
ERG #:	N/A	Max container size for Air Shipments:	N/A		

15. REGULATORY INFORMATION

Federal, State & International Regulations

	SARA 302	-SARA 313-	CERCLA	RCRA	TSCA
Ingredient	RQ	TPQ	List	Chemical Catalog 261.33	8(d)
Glazed/Technical Tile	NO	NO	NO	NO	NO

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No

SARA 311/312: Acute: No; Chronic: No; Fire: NO; Pressure: NO; Reactivity: NO (Mixture / Liquid)

Australian Hazchem Code: None allocated Poison Schedule: None allocated.

WHMIS: This MSDS has been prepared according to the hazard criteria of the Controlled Products

Regulations (CPR) and the MSDS contains all of the information required by the CPR.

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA). This material or all of its components are listed on the Canadian Domestic Substances List (DSL). This material or all of its components are listed (or considered as having been notified) on the European Inventory of Existing Chemical Substances (EINECS). Other inventory lists: ENCS (Japan), Korea, Australia, China (Draft), PICCS (Philippines), Japan (ENCS).

16. OTHER INFORMATION

Prepared By: Luis Omar Navarro

Supersedes Date: New

This Safety Data Sheet (SDS) has been reviewed to fully comply with the guidance contained in the ANSI SDS standard (ANSI Z400.1-2004).

This information is furnished gratuitously and independent of the sales of the product without warranty, expressed or implied,

except that it is accurate to the best knowledge of ILVA S.A. NO WARRANTY, EITHER EXPRESS OR IMPLIED, WHETHER OF

MERCHANTABILITY OF FITNESS OF ANY NATURE OR OTHERWISE WITH RESPECT TO THE PRODUCT OR TO THE DATA

HEREIN IS MADE HEREUNDER. The data in this Material Safety Data Sheet relates only to the specific material designated

herein. It does not relate to use in combination with any other material or in any process.